



## HYDROCARBON EMISSION DETECTION SURVEY OF UINTA BASIN OIL AND GAS WELLS

---

### FINAL REPORT

**Seth Lyman**

**Trang Tran**

**Marc Mansfield**

Bingham Research Center

Utah State University

320 N Aggie Blvd

Vernal, UT 84078

**Arvind Ravikumar**

Department of Energy Resources Engineering

Stanford University

367 Panama St

Stanford, CA 94305

**DOCUMENT NUMBER:** BRC\_180908A

**REVISION:** DRAFT FOR REVIEW

**DATE:** 08 SEPTEMBER 2018

## Executive Summary

We used FLIR GF320 infrared leak detection cameras to detect hydrocarbon emissions from oil and natural gas wells in Utah's Uinta Basin. The purposes of this study were to (1) better understand the sources of hydrocarbons from the oil and gas industry and (2) investigate different emissions detection approaches. We surveyed 3,428 oil and gas facilities from a helicopter in February and March 2018, including well pads, compressor stations, and gas plants (though emissions were only observed from well pads). We also surveyed from the ground 419 of the same well pads that were part of the helicopter survey.

**Commented [CKB1]:** Consistent terminology ... infrared (cameras) vs. optical gas imaging

**Commented [CKB2]:** Table 3-7 sums to 3,225

This study was funded by the Bureau of Land Management, the Utah Legislature, the Utah Division of Air Quality, and the U.S. Environmental Protection Agency. A steering committee consisting of representatives from the Ute Indian Tribe, the Bureau of Land Management, the Utah Division of Air Quality, and the U.S. Environmental Protection Agency worked with our research team to plan the study and guide its execution.

The study's major conclusions include:

- Cold temperatures dramatically reduce the detectable emission rate of infrared leak detection cameras, especially when cameras are used from an aerial platform. The aerial portion of this study detected less than 1/10<sup>th</sup> the number of emission plumes that were observed in a similar study performed during summer months and had a detection limit that was between 2.5 and 7 times worse.
- Ground-based infrared camera surveys are able to detect much smaller emissions than aerial surveys. During the ground survey, we detected emissions at 31% of well pads, compared to 0.5% of pads during the aerial survey, and the detection limit for our camera, when used from the ground, was at least 10 times better than when the camera was used from the helicopter.
- Well pads with detected emissions during the ground and aerial surveys had higher oil and gas production, were younger, and had more liquid storage tanks per pad relative to the entire surveyed population.
- The majority of observed emission plumes were from liquid storage tanks (75.9% of all observed plumes), i.e. emissions from pressure relief devices like thief hatches or pressure relief valves on the tank or on tank piping conveying emissions to a control device, and from tank vent piping (e.g. a manual depressurization valve left open) including emissions from thief hatches, pressure relief valves, and tank piping.
- Well pads with emissions control devices to reduce emissions from tanks were more likely to have detected emissions, had more detected emissions per pad, and were more likely to have emission plumes that were qualitatively categorized as large. Emissions from pads with tank controls originated mostly from tanks.
- Repairs made by oil and gas companies in response to emissions detected ranged from small maintenance and repair work that cost between zero and a few hundred dollars, to replacement of thief hatches that cost several thousand dollars. Most repairs reported cost well under \$1,000.



## Contents

---

[ TOC \o "1-2" \h \z \u ]

## List of Tables

---

[ TOC \h \z \t "Table,1" ]

## List of Figures

---

[ TOC \h \z \t "Figure,1" ]

## 1. Introduction

Optical gas imaging cameras visualize a narrow band of the infrared spectrum in which methane and other hydrocarbons are absorptive (between 3 and 4  $\mu\text{m}$ , depending on the make and model of the camera), allowing users to visualize ~~visible~~ hydrocarbon emission plumes that are invisible to the human eye. These cameras allow users to quickly and definitively locate natural gas leaks from oil and gas industry facilities and equipment. Use of these cameras within the oil and gas industry is widespread. New U.S. Environmental Protection Agency regulations require semi-annual leak detection and repair at most oil and gas wells constructed after June 2017 [ ADDIN EN.CITE <EndNote><Cite><Author>CFR</Author><Year>2016</Year><RecNum>984</RecNum><DisplayText>(CF R, 2016)</DisplayText><record><rec-number>984</rec-number><foreign-keys><key app="EN" db-id="v22aw5p0kf5fpve0sr8xxreie02sxs9z202x" timestamp="1532620378">984</key></foreign-keys><ref-type name="Report">27</ref-type><contributors><authors><author>CFR</author></authors></contributors><titles><title>CFR Title 40, Part 60, Subparts OOOO and OOOOa</title></titles><dates><year>2016</year></dates><urls><related-urls><url>https://www.gpo.gov/fdsys/pkg/FR-2016-06-03/pdf/2016-11971.pdf</url></related-urls></urls></record></Cite></EndNote>], and they allow operators to use optical gas imaging for this purpose. Government agencies also use optical gas imaging cameras for regulatory compliance inspections.

Scientific studies have shown the utility of optical gas imaging technology [ ADDIN EN.CITE ADDIN EN.CITE.DATA ] and have highlighted challenges to their use. This technology is qualitative, and the minimum detectable leak rate of optical gas imaging cameras is variable. Ultimately, the detectable leak rate depends on the amount of contrast in the camera image between the plume and the background behind the plume. Factors that influence contrast between the plume and the background include plume conditions (plume temperature, density and composition), the conditions of the background (surface temperature, reflectivity, and insolation), meteorology (which impacts both plume and background conditions), the distance of the camera from the emission source, camera settings, and on the operator's experience and visual acuity [ ADDIN EN.CITE ADDIN EN.CITE.DATA ].

Two previous optical gas imaging surveys of emissions from oil and gas production facilities have been conducted in Utah's Uinta Basin. The first was a helicopter-based survey conducted during summer 2014 by Lyon et al. [ ADDIN EN.CITE <EndNote><Cite ExcludeAuth="1"><Author>Lyon</Author><Year>2016</Year><RecNum>700</RecNum><DisplayText>(2016)</DisplayText><record><rec-number>700</rec-number><foreign-keys><key app="EN" db-id="v22aw5p0kf5fpve0sr8xxreie02sxs9z202x" timestamp="1472841023">700</key></foreign-keys><ref-type name="Journal Article">17</ref-type><contributors><authors><author>Lyon, David R</author><author>Alvarez, Ramón A</author><author>Zavala-Araiza, Daniel</author><author>Brandt, Adam R</author><author>Jackson, Robert B</author><author>Hamburg, Steven P</author></authors></contributors><titles><title>Aerial surveys of elevated hydrocarbon emissions from oil and gas production sites</title><secondary-title>Environmental science & technology</secondary-title></titles><periodical><full-title>Environmental Science & Technology</full-title><abbr-1>Environ. Sci. Technol.</abbr-1><abbr-2>Environ Sci Technol</abbr-2></periodical><pages>4877-4886</pages><volume>50</volume><number>9</number><dates><year>2016</year></dates><isbn>0

013-936X</isbn><urls></urls></record></Cite></EndNote>]. Lyon et al. surveyed 1389 well pads over nine days and detected emissions from 6.6% of surveyed pads. Relative to the entire surveyed population, pads with detected emissions were newer, higher producing and were more likely to be oil wells. Almost all of the emissions observed by Lyon et al. were from liquid storage tanks. The second previous survey was a ground-based survey conducted during the summer and fall 2016 by Mansfield et al. [ ADDIN EN.CITE <EndNote><Cite

ExcludeAuth="1"><Author>Mansfield</Author><Year>2017</Year><RecNum>965</RecNum><DisplayText>(2017)</DisplayText><record><rec-number>965</rec-number><foreign-keys><key app="EN" db-id="v22aw5p0kf5fpve0sr8xxreie02sxs9z202x" timestamp="1531948429">965</key></foreign-keys><ref-type name="Report">27</ref-type><contributors><authors><author>Mansfield, M. L.</author><author>Lyman, S. N.</author><author>O'Neil, Trevor</author><author>Anderson, Randy</author><author>Jones, C.</author><author>Tran, H.</author><author>Mathis, J.</author><author>Barickman, P.</author><author>Oswald, W.</author><author>LeBaron, B.</author></authors></contributors><titles><title>Storage Tank Emissions Pilot Project (STEPP): Fugitive Organic Compound Emissions from Liquid Storage Tanks in the Uinta Basin</title></titles><dates><year>2017</year></dates><pub-location>Vernal, Utah</pub-location><publisher>Utah State University</publisher><urls><related-urls><url>https://documents.deq.utah.gov/air-quality/planning/technical-analysis/DAQ-2017-009061.pdf</url></related-urls></urls></record></Cite></EndNote>]. They surveyed 454 wells from the ground at the edge of well pads and detected emissions from 39% of pads surveyed. All of the wells surveyed by Mansfield et al. were oil wells, all were constructed within the previous few years, and all had control devices installed to reduce emissions from liquid storage tanks. As with the Lyon et al. study, the majority of observed emissions in Mansfield et al. study were from liquid storage tanks.

Commented [CKB3]: 1-4 years?

Here we present the results of simultaneous aerial and ground-based optical gas imaging surveys conducted in winter and spring 2018 using methods similar to Lyon et al. [ ADDIN EN.CITE <EndNote><Cite

ExcludeAuth="1"><Author>Lyon</Author><Year>2016</Year><RecNum>700</RecNum><DisplayText>(2016)</DisplayText><record><rec-number>700</rec-number><foreign-keys><key app="EN" db-id="v22aw5p0kf5fpve0sr8xxreie02sxs9z202x" timestamp="1472841023">700</key></foreign-keys><ref-type name="Journal Article">17</ref-type><contributors><authors><author>Lyon, David R</author><author>Alvarez, Ramón A</author><author>Zavala-Araiza, Daniel</author><author>Brandt, Adam R</author><author>Jackson, Robert B</author><author>Hamburg, Steven P</author></authors></contributors><titles><title>Aerial surveys of elevated hydrocarbon emissions from oil and gas production sites</title><secondary-title>Environmental science & technology</secondary-title></titles><periodical><full-title>Environmental Science & Technology</full-title><abbr-1>Environ. Sci. Technol.</abbr-1><abbr-2>Environ Sci Technol</abbr-2></periodical><pages>4877-4886</pages><volume>50</volume><number>9</number><dates><year>2016</year></dates><isbn>0 013-936X</isbn><urls></urls></record></Cite></EndNote>] and Mansfield et al. [ ADDIN EN.CITE <EndNote><Cite

ExcludeAuth="1"><Author>Mansfield</Author><Year>2017</Year><RecNum>965</RecNum><DisplayText>(2017)</DisplayText><record><rec-number>965</rec-number><foreign-keys><key app="EN" db-id="v22aw5p0kf5fpve0sr8xxreie02sxs9z202x" timestamp="1531948429">965</key></foreign-keys><ref-type name="Report">27</ref-type><contributors><authors><author>Mansfield, M. L.</author><author>Lyman, S. N.</author><author>O'Neil, Trevor</author><author>Anderson,

# UtahStateUniversity

BINGHAM RESEARCH CENTER

Randy Jones, C. Tran, H. Mathis, J. Barickman, P. Oswald, W. LeBaron, B. /authors></contributors><title>Storage Tank Emissions Pilot Project (STEPP): Fugitive Organic Compound Emissions from Liquid Storage Tanks in the Uinta Basin</title></titles><dates><year>2017</year></dates><pub-location>Vernal, Utah</pub-location><publisher>Utah State University</publisher><urls><related-urls><url>https://documents.deq.utah.gov/air-quality/planning/technical-analysis/DAQ-2017-009061.pdf</url></related-urls></urls></record></Cite></EndNote>], respectively. We compare the results from aerial and ground-based survey platforms, make comparisons among all the optical gas imaging surveys that have been conducted in the Uinta Basin, and investigate the impacts of meteorological and surface conditions, well pad properties, pad ownership, and other factors on the frequency and qualitative size of detected emissions.

Table providing summary of all the optical gas imaging surveys in the Uinta Basin:

	<u>Aerial IR Survey</u>	<u>Ground IR Survey A</u>	<u>Ground IR Survey B</u>	<u>STEPP - Ground IR Survey</u>	<u>Lyon et al - Aerial IR Survey</u>
<u>Date of Survey</u>	<u>Feb-Mar 2018</u>	<u>Feb-Mar 2018</u>	<u>Apr-May 2018</u>	<u>Oct 2016</u>	<u>Aug 2014</u>
<u># Wellpad Facilities Observed</u>	<u>3,428</u>	<u>419</u>			<u>1,389</u>
<u># Wellpad Facilities w/ Observed Emissions</u>	<u>16</u>	<u>129</u>			
<u>% of Wellpad Facilities w/ Observed Emissions</u>	<u>0.5%</u>	<u>31%</u>		<u>39%</u>	
<u># Wellpad Facilities w/ Controlled Tanks</u>		<u>133+</u>			



% of Wellpad Facilities w/ Controlled Tanks w/ Observed Emissions		45%	39%	
--	--	-----	-----	--

## 2. Methods

### 2.1. Aerial Survey

We contracted with Leak Surveys, Inc. to conduct the aerial survey in late February and early March 2018. They used a FLIR GF320 camera from a helicopter at about 75 m above ground to survey for leaks at 3,428 oil and gas facilities, including well pads, compressor stations, and gas processing plants. 652 of the pads surveyed were also surveyed by Lyon et al. [ ADDIN EN.CITE <EndNote><Cite ExcludeAuth="1"><Author>Lyon</Author><Year>2016</Year><RecNum>700</RecNum><DisplayText>(2016)</DisplayText><record><rec-number>700</rec-number><foreign-keys><key app="EN" db-id="v22aw5p0kf5fpve0sr8xxreie02sxs9z202x" timestamp="1472841023">700</key></foreign-keys><ref-type name="Journal Article">17</ref-type><contributors><authors><author>Lyon, David R</author><author>Alvarez, Ramón A</author><author>Zavala-Araiza, Daniel</author><author>Brandt, Adam R</author><author>Jackson, Robert B</author><author>Hamburg, Steven P</author></authors></contributors><titles><title>Aerial surveys of elevated hydrocarbon emissions from oil and gas production sites</title><secondary-title>Environmental science & technology</secondary-title></titles><periodical><full-title>Environmental Science & Technology</full-title><abbr-1>Environ. Sci. Technol.</abbr-1><abbr-2>Environ Sci Technol</abbr-2></periodical><pages>4877-4886</pages><volume>50</volume><number>9</number><dates><year>2016</year></dates><isbn>0013-936X</isbn><urls></urls></record></Cite></EndNote>] (19% of the facilities in this study, 47% of the pads in the Lyon et al. study). [ REF\_Ref524012313 \h ] shows a photograph of the survey helicopter above the location of a controlled propane release.

Prior to the survey, we designated 29 rectangular areas in which Leak Surveys, Inc. would survey for emissions. These areas encompassed 44% of all producing wells and 50% of compressor stations and gas plants in the Uinta Basin. They included facilities operated by 28 different oil and gas companies. The helicopter survey crew flew back and forth across each area and briefly inspected with the FLIR camera each facility they encountered. If they saw an emission plume, they circled the facility for 90 seconds while recording a video of the plume. They also recorded the latitude and longitude, sources of observed emission plumes, whether people were at the observed facility, and types of equipment at each location where emissions were observed. At every fifth location where emissions were observed, they circled the facility for 4 min while recording a video to investigate whether observed emissions were continuous or intermittent over that period.



Figure [ STYLEREF 1 \s ]-[ SEQ Figure \\* ARABIC \s 1 ]. Photograph of survey helicopter above a controlled propane release location.

## 2.2. Ground Survey<sub>s A & B</sub>

We used a FLIR GF320 camera to conduct the ground survey in February and early March 2018 (Ground Survey A), as well as in April and May 2018 (Ground Survey B). In the Ground Survey A During February and March, the ground survey crew operated in the same rectangular areas and on the same days as the aerial survey, though the ground survey crew visited fewer wells and fewer areas per day. The ground crew only surveyed oil and gas well pads (419 pads). They surveyed from the edge of the well pad. They used a tripod or the vehicle to stabilize the camera and spent several minutes at each well scanning for leaks, including in the camera's high-sensitivity mode. High sensitivity mode improves contrast and visualization of emission plumes, but it creates a grainy image. The aerial survey was not able to operate in high-sensitivity mode because of the difficulty of interpreting images in high-sensitivity mode while the helicopter was moving.

If the ground survey crew detected emissions from any source, they recorded a video of the emissions in High Sensitivity Mode (HSM) and in Auto mode. They made a qualitative determination of whether the observed emission plume was small, medium, or large. They also recorded how many distinct emission sources they observed and the source of the emissions.

At every well pad they encountered, whether emissions were observed or not, the survey crew recorded their distance from the well as determined by a rangefinder. Meteorological instrumentation that measured temperature, humidity, barometric pressure, wind speed and direction, and solar radiation (Ground Survey B April and May only for solar radiation) was mounted to the top of the survey crew's vehicle. Meteorological instrumentation used was calibrated against NIST-traceable standards within the prior 12 months. The crew recorded meteorological information from the measurement

Commented [CKB4]: From the wellhead? The distance from the emission source (e.g. tank)?

instrumentation, as well as whether it was sunny or not at their location (April and May Ground Survey B only), and what type of background was behind the observed emission plume (or behind the tanks at the well pad, if no emission plume was observed; April and May Ground Survey B only). They also recorded the total number of oil, condensate, and/or water tanks they observed.

### 2.3. Steering Committee

A steering committee consisting of representatives from the Ute Indian Tribe, the Bureau of Land Management, the Utah Division of Air Quality, and the U.S. Environmental Protection Agency worked with our research team to plan this study and guide its execution.

### 2.4. Industry Involvement

We provided oil and gas companies whose facilities were surveyed with survey results within about 24 hours of the survey, and we provided videos as soon as we were able. After we sent videos and other final survey information, we asked companies at whose facilities emissions were observed to review the information we provided, visit locations where emissions were observed and provide feedback to us about sources of the observed leaks and any repairs that were made as a result of the survey.

### 2.5. Controlled Propane Releases

To determine the emission rates that were detectable from the helicopter and the ground under different conditions, we released commercial-grade propane (~95% propane) at different emission rates from a 5 cm diameter vertical tube at about 2 m above ground. We measured the emission rate with a Fox model FT3 mass flow meter. All releases were carried out between 14:00 and 15:00 local time. During each release, we measured meteorological conditions with the same system mounted atop the ground survey crew's vehicle.

The ground survey crew viewed propane emissions at a distance of 50 m from the tube with the ground-based camera. The helicopter crew viewed propane emissions at 50 m above ground on the first release day, and at 75 m on subsequent days.

### 2.6. Detection Limit Modeling

We used the method of Ravikumar et al. [ ADDIN EN.CITE <EndNote><Cite ExcludeAuth="1"><Author>Ravikumar</Author><Year>2016</Year><RecNum>981</RecNum><DisplayText>(2016)</DisplayText><record><rec-number>981</rec-number><foreign-keys><key app="EN" db-id="v22aw5p0kf5fpve0sr8xxreie02sxs9z202x" timestamp="1532618364">981</key></foreign-keys><ref-type name="Journal Article">17</ref-type><contributors><authors><author>Ravikumar, Arvind P</author><author>Wang, Jingfan</author><author>Brandt, Adam R</author></authors></contributors><titles><title>Are optical gas imaging technologies effective for methane leak detection?</title><secondary-title>Environmental Science & Technology</secondary-title></titles><periodical><full-title>Environmental Science & Technology</full-title><abbr-1>Environ. Sci. Technol.</abbr-1><abbr-2>Environ Sci Technol</abbr-2></periodical><pages>718-

724</pages><volume>51</volume><number>1</number><dates><year>2016</year></dates><isbn>0013-936X</isbn><urls></urls></record></Cite></EndNote>] (also see Ravikumar and Brandt [ ADDIN EN.CITE <EndNote><Cite

ExcludeAuth="1"><Author>Ravikumar</Author><Year>2017</Year><RecNum>982</RecNum><DisplayText>(2017)</DisplayText><record><rec-number>982</rec-number><foreign-keys><key app="EN" db-id="v22aw5p0kf5fpve0sr8xxreie02sxs9z202x" timestamp="1532619316">982</key></foreign-keys><ref-type name="Journal Article">17</ref-type><contributors><authors><author>Ravikumar, Arvind P</author><author>Brandt, Adam R</author></authors></contributors><titles><title>Designing better methane mitigation policies: the challenge of distributed small sources in the natural gas sector</title><secondary-title>Environmental Research Letters</secondary-title></titles><periodical><full-title>Environmental Research Letters</full-title></periodical><pages>044023</pages><volume>12</volume><number>4</number><dates><year>2017</year></dates><isbn>1748-9326</isbn><urls></urls></record></Cite></EndNote>] and Ravikumar et al. [ ADDIN EN.CITE <EndNote><Cite

ExcludeAuth="1"><Author>Ravikumar</Author><Year>2018</Year><RecNum>922</RecNum><DisplayText>(2018)</DisplayText><record><rec-number>922</rec-number><foreign-keys><key app="EN" db-id="v22aw5p0kf5fpve0sr8xxreie02sxs9z202x" timestamp="1523979648">922</key></foreign-keys><ref-type name="Journal Article">17</ref-type><contributors><authors><author>Ravikumar, Arvind P</author><author>Wang, Jingfan</author><author>McGuire, Mike</author><author>Bell, Clay S</author><author>Zimmerle, Daniel</author><author>Brandt, Adam R</author></authors></contributors><titles><title>Good versus Good Enough? Empirical tests of methane leak detection sensitivity of a commercial infrared camera</title><secondary-title>Environmental science & technology</secondary-title></titles><periodical><full-title>Environmental Science & Technology</full-title><abbr-1>Environ. Sci. Technol.</abbr-1><abbr-2>Environ Sci Technol</abbr-2></periodical><dates><year>2018</year></dates><isbn>0013-936X</isbn><urls></urls></record></Cite></EndNote>]) to model the relationship between apparent ground temperature and detection limits during the aerial survey and for the time period of the Lyon et al. [ ADDIN EN.CITE <EndNote><Cite

ExcludeAuth="1"><Author>Lyon</Author><Year>2016</Year><IDText>Aerial surveys of elevated hydrocarbon emissions from oil and gas production sites</IDText><DisplayText>(2016)</DisplayText><record><isbn>0013-936X</isbn><titles><title>Aerial surveys of elevated hydrocarbon emissions from oil and gas production sites</title><secondary-title>Environmental science & technology</secondary-title></titles><pages>4877-4886</pages><number>9</number><contributors><authors><author>Lyon, David R</author><author>Alvarez, Ramón A</author><author>Zavala-Araiza, Daniel</author><author>Brandt, Adam R</author><author>Jackson, Robert B</author><author>Hamburg, Steven P</author></authors></contributors><added-date format="utc">1472841612</added-date><ref-type name="Journal Article">17</ref-type><dates><year>2016</year></dates><rec-number>700</rec-number><last-updated-date format="utc">1472841612</last-updated-date><volume>50</volume></record></Cite></EndNote>] study. The Ravikumar model uses measured meteorological conditions and surface properties to simulate radiance from the plume and the background. Plume composition, leak size distribution, and distance from the plume are taken into account in the model.

## 2.7. Data Access, Processing, and Analysis

We obtained oil and gas facility information from the Utah Division of Oil, Gas and Mining [ ADDIN EN.CITE

<EndNote><Cite><Author>UDOGM</Author><Year>2018</Year><RecNum>161</RecNum><DisplayText>(UDOGM, 2018)</DisplayText><record><rec-number>161</rec-number><foreign-keys><key app="EN" db-id="v22aw5p0kf5fpve0sr8xxreie02sxs9z202x" timestamp="1426004954">161</key></foreign-keys><ref-type name="Web Page">12</ref-type><contributors><authors><author>UDOGM</author></authors></contributors><titles><title>http://oilgas.ogm.utah.gov/Data\_Center/DataCenter.cfm</title><short-title>http://oilgas.ogm.utah.gov/Data\_Center/DataCenter.cfm</short-title></titles><volume>2015</volume><number>3/10/2015</number><dates><year>2018</year><pub-dates><date>7/21/2018</date></pub-dates></dates><pub-location>Salt Lake City, Utah</pub-location><publisher>Utah Division of Oil, Gas and Mining</publisher><urls><related-urls><url>http://oilgas.ogm.utah.gov/Data\_Center/DataCenter.cfm</url></related-urls></urls><custom1>2015</custom1><custom2>3/10/2015</custom2></record></Cite></EndNote>].

The aerial survey crew only recorded survey locations when emissions were detected, so we followed the method of Lyon et al. [ ADDIN EN.CITE <EndNote><Cite ExcludeAuth="1"><Author>Lyon</Author><Year>2016</Year><RecNum>700</RecNum><DisplayText>(2016)</DisplayText><record><rec-number>700</rec-number><foreign-keys><key app="EN" db-id="v22aw5p0kf5fpve0sr8xxreie02sxs9z202x" timestamp="1472841023">700</key></foreign-keys><ref-type name="Journal Article">17</ref-type><contributors><authors><author>Lyon, David R</author><author>Alvarez, Ramón A</author><author>Zavala-Araiza, Daniel</author><author>Brandt, Adam R</author><author>Jackson, Robert B</author><author>Hamburg, Steven P</author></authors></contributors><titles><title>Aerial surveys of elevated hydrocarbon emissions from oil and gas production sites</title><secondary-title>Environmental science & technology</secondary-title></titles><periodical><full-title>Environmental Science & Technology</full-title><abbr-1>Environ. Sci. Technol.</abbr-1><abbr-2>Environ Sci Technol</abbr-2></periodical><pages>4877-4886</pages><volume>50</volume><number>9</number><dates><year>2016</year></dates><isbn>0 013-936X</isbn><urls></urls></record></Cite></EndNote>] to produce a dataset of all the wells within the survey area. We excluded wells that were not producing (using February 2018 production data) and we aggregated well information to the pad level since wells on multiple-well pads with shared equipment were counted as a single facility by the aerial survey crew.

In addition to the meteorological data collected for the ground survey, we used data from the Vernal airport to compare meteorological conditions during this study to those during the Lyon et al. [ ADDIN EN.CITE <EndNote><Cite

ExcludeAuth="1"><Author>Lyon</Author><Year>2016</Year><RecNum>700</RecNum><DisplayText>(2016)</DisplayText><record><rec-number>700</rec-number><foreign-keys><key app="EN" db-id="v22aw5p0kf5fpve0sr8xxreie02sxs9z202x" timestamp="1472841023">700</key></foreign-keys><ref-type name="Journal Article">17</ref-type><contributors><authors><author>Lyon, David R</author><author>Alvarez, Ramón A</author><author>Zavala-Araiza, Daniel</author><author>Brandt, Adam R</author><author>Jackson, Robert B</author><author>Hamburg, Steven P</author></authors></contributors><titles><title>Aerial surveys of elevated hydrocarbon emissions from oil and gas production sites</title><secondary-

**Commented [CKB5]:** It's not clear to me how you did this. I'm not sure it needs to be. I can't recall if Lyon et al described how they did this in their paper or whether you just learned directly from David Lyon how to do the aggregation in a manner similar to his.

title>Environmental science & technology</secondary-title></titles><periodical><full-  
title>Environmental Science & Technology</full-title><abbr-1>Environ. Sci. Technol.</abbr-  
1><abbr-2>Environ Sci Technol</abbr-2></periodical><pages>4877-  
4886</pages><volume>50</volume><number>9</number><dates><year>2016</year></dates><isbn>0  
013-936X</isbn><urls></urls></record></Cite></EndNote>] survey, and for detection limit modeling.  
The Vernal airport is the only station in the Uinta Basin at which sky cover information is collected. We  
obtained Vernal airport data from the National Climatic Data Center [ ADDIN EN.CITE  
<EndNote><Cite><Author>NCDC</Author><Year>2018</Year><RecNum>219</RecNum><DisplayText>{  
NCDC, 2018}</DisplayText><record><rec-number>219</rec-number><foreign-keys><key app="EN" db-  
id="v22aw5p0kf5fpve0sr8xxreie02sxs9z202x" timestamp="1441379052">219</key></foreign-  
keys><ref-type name="Web Page">12</ref-  
type><contributors><authors><author>NCDC</author></authors></contributors><titles><title>Nationa  
l Climatic Data  
Center</title></titles><volume>2018</volume><number>July</number><dates><year>2018</year></  
dates><publisher>National Oceanic and Atmospheric Administration</publisher><urls><related-  
urls><url>https://www.ncdc.noaa.gov/</url></related-urls></urls></record></Cite></EndNote>]. We  
used the MODIS Terra 500 m snow cover dataset [ ADDIN EN.CITE  
<EndNote><Cite><Author>MODIS</Author><Year>2018</Year><RecNum>985</RecNum><DisplayText>  
(MODIS, 2018)</DisplayText><record><rec-number>985</rec-number><foreign-keys><key app="EN"  
db-id="v22aw5p0kf5fpve0sr8xxreie02sxs9z202x" timestamp="1533595854">985</key></foreign-  
keys><ref-type name="Web Page">12</ref-  
type><contributors><authors><author>MODIS</author></authors></contributors><titles><title>MODI  
S Snow  
Cover</title></titles><volume>2018</volume><dates><year>2018</year></dates><urls><related-  
urls><url>https://modis.gsfc.nasa.gov/data/dataproduct/mod10.php</url></related-  
urls></urls></record></Cite></EndNote>] to determine average percent snow cover for each area on  
each day of the aerial survey. For days during which a survey area had less than 50% data coverage in  
the MODIS dataset, we assumed that (1) the snow cover on the missed day was the average of the days  
before and after, or (2) the daily rate of change in snow cover in that area was the same as other survey  
areas with similar percent snow cover.

Average values are shown as average  $\pm$  95% confidence interval.

We calculated two metrics to characterize the statistics of observed emissions during the ground survey.  
These were (1) the number of observed emission plumes per well pad, and (2) a “severity score,”  
intended to convey the qualitative size of emissions as observed by the survey crew. For the severity  
score, we assigned a value of 1 for plumes categorized as small, 2 for medium, and 3 for large. An  
average value was calculated for each well pad at which at least one emission is observed.

### 2.7.1. Monte Carlo Analysis of Company Performance

We used Monte Carlo analysis to answer this question about the plumes per pad and severity score  
metrics: When a metric for any particular company was smaller or larger than the overall result, was  
that merely a chance occurrence, or can we take it as evidence of underperformance or outperformance  
in emission suppression by one company relative to the others? We applied the following p-test to  
identify statistically significant departures by individual companies from the overall metrics. The

complete ground surveys. A&B included 419 well pads. Assume that  $M$  of these belong to company X. Let  $m_c$  be the value of one of the metrics evaluated over these  $M$  well pads. Then we take a large number ( $10^6$ ) of independent, random subsets of the  $N$  well pads, each subset containing  $M$  well pads. Let  $m_R$  represent the value of the same metric for the random subsets. Then let  $p$  be the fraction of the time that the  $m_R$  values are less than  $m_c$ . We interpret this  $p$  as the probability that a random selection of  $M$  well pads outperforms the  $M$  well pads belonging to company X. Therefore,  $p$  near zero and one, respectively, means that company X outperforms and underperforms the pack, respectively, in emission suppression. If we accept the traditional threshold of 95% confidence, then  $p < 0.05$  represents statistically significant outperformance, while  $p > 0.95$  implies statistically significant underperformance, while any  $p$  between 0.05 and 0.95 is not strong evidence either way. (But  $p$  values always need to be taken with a grain of salt. At the 95%-confidence level, there are 1-in-20 odds that we will misjudge any one company, and exactly 20 companies are represented in the study.)

**Commented [CKB6]:** Is this commonly understood about  $p$  values? If so, do we need to say here?

### 3. Results

#### 3.1. Controlled Propane Releases

[ REF\_Ref524012337 \h ] provides information about the propane releases we conducted. The qualitative detectability of the propane plume from the helicopter did not appear to be dependent on the emission rate. The  $5.04 \text{ g s}^{-1}$  plume was less visible than that  $1.89 \text{ g s}^{-1}$  plume, in spite of being more than twice as large, perhaps because of the difference in helicopter height or the difference in meteorological conditions. The emitted propane plumes were clearly detectable with the ground camera (at a distance of 50 m) for all of the propane releases, the lowest of which was  $0.14 \text{ g s}^{-1}$ , though qualitative detectability appeared to be better on 28 February and 1 March than on 26 February. [ REF\_Ref524012360 \h ] and [ REF\_Ref524012371 \h ] show still images from the propane release conducted on 1 March. All the propane release videos are available at [ HYPERLINK "https://usu.box.com/v/2018-USU-IRsurvey" ].

**Table [ STYLEREf 1 \s ]-[ SEQ Table \\* ARABIC \s 1 ]. Information about controlled propane releases conducted to determine detectable emission rates.**

Height indicates the approximate height above ground of the helicopter.

Date	Emission Rate ( $\text{g s}^{-1}$ )	Temperature ( $^{\circ}\text{C}$ )	Wind Speed ( $\text{m s}^{-1}$ )	Snow Cover	Height (m)	Plume in Aerial Video
26 Feb 2018	1.89	5.7	0.7	~80%	50	Faint, consistent
28 Feb 2018	5.04	7.2	1.2	Patchy, ~70%	75	Faint, inconsistent
1 Mar 2018	3.49	5.5	1.1	Patchy, ~50%	75	Clear, consistent
1 Mar 2018	3.21	5.4	1.3	Patchy, ~50%		
1 Mar 2018	2.14	5.1	1.1	Patchy, ~50%		
1 Mar 2018	1.52	5.1	1.1	Patchy, ~50%		
1 Mar 2018	0.80	5.1	1.1	Patchy, ~50%		
1 Mar 2018	0.24	5.1	1.1	Patchy, ~50%		
1 Mar 2018	0.14	5.1	1.1	Patchy, ~50%		




Figure [ STYLEREf 1 \s ]-[ SEQ Figure \\* ARABIC \s 1 ]. Infrared image taken from the ground on 1 March 2018 of propane being released from a tube during controlled propane release tests.



Figure [ STYLEREf 1 \s ]-[ SEQ Figure \\* ARABIC \s 1 ]. Aerial Infrared image taken from the helicopter on 1 March 2018 of propane being released from a tube during controlled propane release tests.

### 3.2. Survey Overview

Of the 3,428 oil and gas facilities in the Aerial Survey, emission plumes were only detected at 16 (0.5%), all of which were producing oil and gas well pads. Emissions were detectable at 129 of the 419 well pads visited during the Ground Surveys A&B campaign (31%). A total of 198 emission plumes, or



## UtahStateUniversity<sup>®</sup>

BINGHAM RESEARCH CENTER

0.47 plumes per pad, were observed in the ground survey (some pads had none and others had multiple detected emission plumes).

Seven out of eleven companies responded to our request for information about the observations in the Aerial and Ground Surveys results ([ REF \_Ref524100239 \h ] and [ REF \_Ref524012465 \h ]). Of the four that did not respond, two had recently sold their assets in the Uinta Basin to another party, but the new ownership information was not available at the time of the survey. We received responses for 81% of the well pads at which we observed emissions in the aerial survey and 90% of the well pads at which we observed emissions in the ground survey.

[ REF \_Ref524012408 \h ], [ REF \_Ref524012428 \h ], and [ REF \_Ref524012434 \h ] provide example still images from videos collected during the survey. The Aerial and Ground survey videos in these figures were from the same well pad, though the ground survey was conducted about two months after the aerial survey. The videos from which these still images were taken are available at [ HYPERLINK "<https://usu.box.com/v/2018-USU-IRsurvey>" ].



Figure [ STYLEREFF 1 \s ]-[ SEQ Figure \\* ARABIC \s 1 ]. Infrared image taken from the helicopter at a well pad during the aerial survey.




Figure [ STYLEREF 1 \s ]-[ SEQ Figure \\* ARABIC \s 1 ]. Infrared image taken from the ground at a well pad during the Aerial Survey.

The emission source in this figure is the same as in [ REF \_Ref524012408 \h ].




Figure [ STYLEREF 1 \s ]-[ SEQ Figure \\* ARABIC \s 1 ]. Infrared image taken in high sensitivity mode from the ground at a well pad during the Aerial Survey.

This is an image of the same source shown in [ REF \_Ref524012408 \h ] and [ REF \_Ref524012428 \h ].

### 3.3. Meteorology

#### 3.3.1. Aerial Survey

Average conditions were calm, cold, and clear during the aerial survey, with daytime wind speed of  $1.4 \pm 0.0 \text{ m s}^{-1}$  (average  $\pm 95\%$  confidence interval of survey days), daytime temperature of  $-2.9 \pm 2.3^\circ\text{C}$ , and skies that were reported as clear for  $92 \pm 7\%$  of daytime hours on survey days. Wind speeds ranged between 0 and  $4.0 \text{ m s}^{-1}$ . Daytime average temperatures varied between  $-9.1$  and  $2.6^\circ\text{C}$ . Average hourly visibility was greater than 10 km on all survey days. Snow cover was  $0.5 \pm 0.6\%$  in surveyed areas on survey days, and ranged between 0 and 8%. The number of emission plumes detected per pad on each aerial survey day was not correlated with daily meteorological conditions.

**Commented [CKB7]:** Why does this number have an associated uncertainty, but the 5 clear days for the Ground Survey (70% highlighted below) does not?

**Commented [CKB8]:** r2, p-values??

#### 3.3.2. Ground Survey: A & B

The February and March portion of the ground survey was conducted on the same days as the Aerial Survey, so the conditions were identical for both surveys. During Ground Survey B the April and May portion of the ground survey, wind speed at survey locations, temperature at survey locations, and percent of survey locations where it was reported to be sunny were  $3.0 \pm 0.2 \text{ m s}^{-1}$ ,  $18.0 \pm 0.7^\circ\text{C}$ , and 70%, respectively. No snow cover existed during Ground Survey B April and May.

We examined the impacts of ambient meteorological conditions (wind speed, temperature and cloudiness) and background conditions behind detected plumes or behind liquid storage tanks on emissions detected during the Ground Surveys A & B. Under calm to light breeze conditions (wind speeds between 0 and  $3.5 \text{ m s}^{-1}$ ), emission detections were negatively and significantly correlated with wind speed (e.g., stronger wind tended to dilute plumes, making it less likely that the camera would detect a plume;  $r^2 = 0.80$ ;  $p < 0.01$ ), as was shown by Ravikumar and Brandt [ ADDIN EN.CITE

<EndNote><Cite  
ExcludeAuth="1"><Author>Ravikumar</Author><Year>2017</Year><RecNum>982</RecNum><DisplayText>(2017)</DisplayText><record><rec-number>982</rec-number><foreign-keys><key app="EN" db-id="v22aw5p0kf5fpve0sr8xxreie02sxs9z202x" timestamp="1532619316">982</key></foreign-keys><ref-type name="Journal Article">17</ref-type><contributors><authors><author>Ravikumar, Arvind P</author><author>Brandt, Adam R</author></authors></contributors><titles><title>Designing better methane mitigation policies: the challenge of distributed small sources in the natural gas sector</title><secondary-title>Environmental Research Letters</secondary-title></titles><periodical><full-title>Environmental Research Letters</full-title></periodical><pages>044023</pages><volume>12</volume><number>4</number><dates><year>2017</year></dates><isbn>1748-9326</isbn><urls></urls></record></Cite></EndNote>]. However, this correlation did not hold true when wind speed was above  $3.5 \text{ m s}^{-1}$  [ REF \_Ref524012513 \h ]. Similarly, at a lower range of ambient temperatures (between 0 and  $20^\circ\text{C}$ ), the percent of pads with detectable emissions increased as temperature increased ( $r^2 = 0.63$ ;  $p < 0.05$ ; [ REF \_Ref524012534 \h ]), as was shown by Ravikumar et al. [ ADDIN EN.CITE <EndNote><Cite  
ExcludeAuth="1"><Author>Ravikumar</Author><Year>2016</Year><IDText>Are optical gas imaging technologies effective for methane leak

detection?</IDText><DisplayText>(2016)</DisplayText><record><isbn>0013-936X</isbn><titles><title>Are optical gas imaging technologies effective for methane leak detection?</title><secondary-title>Environmental Science & Technology</secondary-title></titles><pages>718-724</pages><number>1</number><contributors><authors><author>Ravikumar, Arvind P</author><author>Wang, Jingfan</author><author>Brandt, Adam R</author></authors></contributors><added-date format="utc">1532618953</added-date><ref-type name="Journal Article">17</ref-type><dates><year>2016</year></dates><rec-number>981</rec-number><last-updated-date format="utc">1532618953</last-updated-date><volume>51</volume></record></Cite></EndNote>]. Above this range, temperature did not seem to have an effect on emissions detection (Figure 8).




Figure [ STYLERE 1 \s ]-[ SEQ Figure \\* ARABIC \s 1 ]. Percent of pads with detected emissions in Ground Surveys A&B versus wind speed.

The x-axis is organized by decile, and the median of each decile is shown.





Figure [ STYLERE 1 \s ]-[ SEQ Figure \\* ARABIC \s 1 ]. Percent of pads with detected emissions in Ground Surveys A&B versus ambient temperature.

The x-axis is organized by decile, and the median of each decile is shown.

[ REF\_Ref524012550 \h ] shows that sunny conditions yielded more detected emissions than cloudy conditions. Sunny conditions allow for more surface heating, creating better contrast between the plume and the background if the ground is used as a background. Clear sky conditions also provide better contrast if the sky is used as a background [ ADDIN EN.CITE <EndNote><Cite><Author>Ravikumar</Author><Year>2016</Year><RecNum>981</RecNum><DisplayText>(Ravikumar et al., 2016)</DisplayText><record><rec-number>981</rec-number><foreign-keys><key app="EN" db-id="v22aw5p0kf5fpve0sr8xxreie02sxs9z202x" timestamp="1532618364">981</key></foreign-keys><ref-type name="Journal Article">17</ref-type><contributors><authors><author>Ravikumar, Arvind P</author><author>Wang, Jingfan</author><author>Brandt, Adam R</author></authors></contributors><titles><title>Are optical gas imaging technologies effective for methane leak detection?</title><secondary-title>Environmental Science & Technology</secondary-title></titles><periodical><full-title>Environmental Science & Technology</full-title><abbr-1>Environ. Sci. Technol.</abbr-1><abbr-2>Environ Sci Technol</abbr-2></periodical><pages>718-724</pages><volume>51</volume><number>1</number><dates><year>2016</year></dates><isbn>0013-936X</isbn></Cite></EndNote>].



**Figure [ STYLEREf 1 \s ]-[ SEQ Figure \\* ARABIC \s 1 ]. Impact of sunny or cloudy conditions on the number of emission plumes detected per well pad in the Ground Surveys A&B.**

This information was only collected in April and May. Tops of bars are averages, and whiskers represent 95% confidence intervals.

Four categories of background were reported by the Ground Survey crew: clouds, clear skies, ground (i.e., when looking down on the site from a higher location), and hillside (i.e., hills behind the well pad). [ REF\_Ref524012565 \h ] shows that when the ground was used as background, fewer emission plumes were detected than when clouds or clear sky were used as a background, while a hillside background was associated with the highest detection rate among the four background types. However, these differences were not significant at the 95% confidence level. The ground and hillside background types had few surveyed pads (12 and 14 surveyed pads, respectively), leading to large confidence intervals.




Figure [ STYLEREf 1 \s ]-[ SEQ Figure \\* ARABIC \s 1 ]. Impact of the background behind the plume (or behind tanks, if no plume was detected) on the number of emission plumes detected per well pad.

This information was only collected in Ground Survey B (April and May). Tops of bars are averages, and whiskers represent 95% confidence intervals.

### 3.4. Sources of Observed Emissions

Sources of observed emissions were derived from notes made by reviewing aerial IR videos and the ground survey crew and responses received from companies. 65% of responses indicated that companies observed similar emissions to those found by our Aerial and Ground survey crews, while the other 35% either did not see any emissions in their subsequent inspection or did not see emissions from the same source(s). Two possible reasons exist for discrepancies between the Ground Survey crew's findings and the findings of companies in subsequent inspections: either (1) conditions at the pad changed between the two visits, leading to different emissions outcomes, or (2) one of the two parties was mistaken about the emission source. We assumed that (1) was the case, except when it was clear from information provided by companies that the Ground Survey crew's assessment was in error.

**Commented [CKB9]:** Not sure if this opening paragraph covers the aerial IR observations as well?

**Commented [CKB10]:** Can you provide an example of what would make a ground survey observed plume an error?

#### 3.4.1. Aerial Survey

[ REF\_Ref524100239 \h ] presents details about each well pad at which emissions were detected for the Aerial Survey, including findings from the Ground Surveys A & B (ground survey about two months later) at the same well pads. The Aerial Surveys for the pads presented in [ REF\_Ref524100239 \h ] occurred between 28 February and 10 March, and the Ground Surveys occurred between 16 April and 10 May. The Ground Survey crew visited 15 of the 16 well pads at which emissions were detected from the helicopter. Where companies reported repairs, repairs were reported to have been made within two days of the Aerial Survey, and none of the repairs made involved any cost on the part of the operators.

**Commented [CKB11]:** So, are we just talking Ground Survey B?

[ REF\_Ref524100239 \h ] shows that all but one detected emission plume originated from liquid storage tanks. Repairs that were reported were routine tasks, including closing valves or hatches and making adjustments to control devices. At five of the pads, detected emissions were due to intermittent routine activities, including liquids unloading and activities related to a well workover. The ground survey crew detected emissions at 13 of 15 pads visited, including all the wells at which repairs were

**Commented [CKB12]:** Well liquids unloadings are 'routine', but not continuous. Ditto for well workovers, well maintenance activities.



reported. Of the 11 pads at which detected emissions were not due to liquids unloading or ~~intermittent~~~~routine~~ maintenance, six showed the same source of emissions in both the ~~aerial~~~~Aerial~~ and ~~Ground~~ surveys.

Table [STYLEREFF 1 \s ]-[SEQ Table \\* ARABIC \s 1]. Information about each well pad at which emissions were detected in the Aerial Survey. Leak size is a qualitative determination made by the camera operator.

Com-pany	Pad Type	Tank controls	Aerial Survey			Ground Survey		
			# plumes	Size	Emission source	Repairs made	# plumes	Size
E	Oil	Yes	1	S	Tank vent line	Closed manual valve	1	S
E	Oil	Yes	1	S	Tank vent	Closed manual valve	2	L, M
B	Oil	Yes	1	S	Thief hatch	None	1	L
B	Oil	Yes	1	M	Tank vent—maintenance rig on location	None	None	
B	Oil	Yes	1	L	Tank vent	Adjusted flare regulator pressure	1	L
B	Oil	Yes	2		Tank vent and thief hatch	None	4	L, L, Tank vents and surface piping
B	Oil	Yes	1	L	Tank vent	Reit combustor flame	1	L
B	Oil	Yes	1	L	Tank venting after workover before connection to sales line	None	1	L
L	Oil	No	2	S, M	Thief hatches	No operator response	2	S
L	Oil	Yes	1		Thief hatch	No operator response	2	L
H	Gas	Yes	1		Thief hatch during liquids unloading	None	Not surveyed	
H	Gas	No	1		Thief hatch during liquids unloading	None	None	
F	Oil	No	1	S	Burner exhaust on separator	None	2	M, S
J	Oil	Yes	1		Thief hatch	Latched thief hatch	1	M
K	Gas	No	1		Tank vent	Closed manual valve	1	S
K	Gas	No	2		Tank vents during liquids unloading	None	2	S, S

**Commented [CKB13]:** Is there a distinction between a thief hatch venting in a pressure relief manner versus and open thief hatch?



### 3.4.2. Ground Surveys

We performed statistical analyses with the entire Ground Survey A&B dataset and on a sub-dataset that only included well pads equipped with emission controls on liquid storage tanks. Only pads with tank controls were surveyed in the STEPP study [ ADDIN EN.CITE <EndNote><Cite><Author>Mansfield</Author><Year>2017</Year><RecNum>965</RecNum><DisplayText>(Mansfield et al., 2017)</DisplayText><record><rec-number>965</rec-number><foreign-keys><key app="EN" db-id="v22aw5p0kf5fpve0sr8xxreie02sxs9z202x" timestamp="1531948429">965</key></foreign-keys><ref-type name="Report">27</ref-type><contributors><authors><author>Mansfield, M. L.</author><author>Lyman, S. N.</author><author>O'Neil, Trevor</author><author>Anderson, Randy</author><author>Jones, C.</author><author>Tran, H.</author><author>Mathis, J.</author><author>Barickman, P.</author><author>Oswald, W.</author><author>LeBaron, B.</author></authors></contributors><titles><title>Storage Tank Emissions Pilot Project (STEPP): Fugitive Organic Compound Emissions from Liquid Storage Tanks in the Uinta Basin</title></titles><dates><year>2017</year></dates><pub-location>Vernal, Utah</pub-location><publisher>Utah State University</publisher><urls><related-urls><url>https://documents.deq.utah.gov/air-quality/planning/technical-analysis/DAQ-2017-009061.pdf</url></related-urls></urls></record></Cite></EndNote>], and we include STEPP survey results for comparison where appropriate. The STEPP study was a ground IR survey of XX pads, all with controlled tanks, in October 2016 using an Opgal EyeCGas infrared camera. In Ground Surveys A&B, pads with controlled tanks were identified based on the 2014 Utah air agencies oil and gas emissions inventory [ ADDIN EN.CITE <EndNote><Cite><Author>UDAQ</Author><Year>2018</Year><RecNum>958</RecNum><DisplayText>(UDAQ, 2018)</DisplayText><record><rec-number>958</rec-number><foreign-keys><key app="EN" db-id="v22aw5p0kf5fpve0sr8xxreie02sxs9z202x" timestamp="1528402134">958</key></foreign-keys><ref-type name="Web Page">12</ref-type><contributors><authors><author>UDAQ</author></authors></contributors><titles><title>Uinta Basin: 2014 Air Agencies Oil and Gas Emissions Inventory</title></titles><volume>2018</volume><number>1 June 2018</number><dates><year>2018</year></dates><pub-location>Salt Lake City, Utah</pub-location><urls><related-urls><url>https://deq.utah.gov/legacy/destinations/u/uintah-basin/air-agencies-emissions-inventory/index.htm</url></related-urls></urls></record></Cite></EndNote>], information received from well pad operators, and the ground survey crew's notes. Among the 419 surveyed well pads, we were able to identify 133 pads with controlled tanks. The actual number of well pads with controlled tanks could be higher than 133 because pads newer than 2014 are not included in the 2014 inventory, and because the survey crew only made notes about tank emission controls during Ground Survey B April and May.

Among the 133 pads with controlled tanks, a total of 96 emission plumes were detected at 60 pads (45% of the visited pads), and 0.72 plumes per pad were observed, which was higher than the values for the entire dataset (31% of pads had detected emissions, 0.47 plumes/pad), and also higher than was reported in the STEPP study (39% of the 77 visited pads had detected emissions, 0.43 plumes/pad).

**Commented [CKB14]:** How many wellpads surveyed in STEPP?

[ REF\_Ref524013169 \h ] shows emission sources at the 129 well pads where emission plumes were detected in the Ground Surveys A&B entire dataset. Tank hatches, pressure relief valves and tank vent pipes comprised the majority of emission sources (75.9% of all observed plumes), with emissions detected of all three qualitative sizes. Pads with emission controls on tanks had a similar emissions distribution to the entire dataset. The majority of the large plumes detected were located at well pads with controlled tanks.

These same source categories also made up the majority of detected emissions in the STEPP study. More emission plumes (mostly small) were detected from tank vent pipes in this study than in STEPP, and unidentified sources in this study were only 3%, compared with 8.7% in STEPP. This could be due to the ground survey crew having more experience in this study relative to STEPP (the same operators conducted the survey in both studies). It could also be due to differences in the cameras used (an Opgal EyeCGas was used in STEPP). Dehydrators were important emission sources in this study, but emissions from dehydrators were not reported in STEPP because no wellpads surveyed had glycol dehydrators. In this study, the ground survey crew detected emissions from well heads and an underground pipeline, sources which were also not observed in the STEPP study.

**Commented [CKB15]:** Any ambient conditions differences that could play a role?

**Commented [CKB16]:** Not observed? Or not looked at?

Table [STYLEREF 1 \s ]- SEQ Table \ \* ARABIC \s 1]. Sources and qualitative sizes of observed emissions for the entire dataset, well pads with controlled tanks, and for the STEPP study, which only included pads with controlled tanks.

	Entire dataset					Pads with controlled tanks					STEPP study				
	S	M	L	TOTAL	%	S	M	L	TOTAL	%	S	M	L	TOTAL	%
Thief hatch	19	27	13	59	30.3%	3	11	11	25	26.6%	8	41	44	93	47.4%
Pressure relief valve	24	18	13	55	28.2%	13	9	10	32	34.0%	19	19	15	53	27.0%
Tank vent pipe	18	7	9	34	17.4%	4	5	8	17	18.1%	0	7	5	12	6.1%
Methanol tank	0	0	0	0	0.0%	0	0	0	0	0.0%	6	0	0	6	3.1%
Other valve	0	0	0	0	0.0%	0	0	0	0	0.0%	3	3	0	6	3.1%
Combustor	3	1	2	6	3.1%	3	1	2	6	6.4%	1	2	0	3	1.5%
Pressure relief piping	0	0	0	0	0.0%	0	0	0	0	0.0%	2	0	1	3	1.5%
Flare stack	1	5	1	7	3.6%	0	2	1	3	3.2%	0	0	1	1	0.5%
Possible hole in tank	0	0	0	0	0.0%	0	0	0	0	0.0%	0	1	0	1	0.5%
Shack on site	0	0	0	0	0.0%	0	0	0	0	0.0%	1	0	0	1	0.5%
Unidentified source	2	2	0	4	2.1%	1	2	0	3	3.2%	6	1	10	17	8.7%
Underground pipe	0	1	0	1	0.5%	0	0	0	0	0.0%	--	--	--	--	--
Dehydrator	4	13	3	20	10.3%	1	3	2	6	6.4%	--	--	--	--	--
Chemical pump	0	1	0	1	0.5%	0	0	0	0	0.0%	--	--	--	--	--
Well head	4	1	3	9	4.6%	2	0	0	2	2.1%	--	--	--	--	--
<b>TOTAL</b>	<b>75</b>	<b>76</b>	<b>44</b>	<b>195</b>	<b>100.0%</b>	<b>27</b>	<b>33</b>	<b>34</b>	<b>94</b>	<b>100.0%</b>	<b>46</b>	<b>74</b>	<b>76</b>	<b>196</b>	<b>100.0%</b>

**Commented [CKB17]:** "Entire Dataset" = "Ground Surveys A&B (419 pads)"  
"Pads with Controlled Tanks in Ground Surveys A&B (133 pads)"  
"STEPP study (?? Pads)"

I think it helps hold the numbers together to add # wellpads surveyed to each column heading.

Were methanol tanks looked at in Ground Surveys A&B? (or should these 0s be dashed like dehydrators and wellheads are for STEPP?)

### 3.5. Well Pad Properties

[ REF\_Ref524088163 \h ] shows a comparison of the properties of all surveyed producing well pads and the pads at which emissions were detected. Compared to the entire population of surveyed pads, pads with detected emissions were higher-producing, were younger, and had more tanks per pad.

Table [ STYLEREf 1 \s ]-[ SEQ Table \\* ARABIC \s 1 ]. Comparison of properties of well pads at which emissions were detected versus the entire surveyed population.

(a) indicates data taken from the 2014 Utah air agencies oil and gas emissions inventory [ ADDIN EN.CITE <EndNote><Cite><Author>UDAQ</Author><Year>2018</Year><RecNum>958</RecNum><DisplayText>(UDAQ, 2018)</DisplayText><record><rec-number>958</rec-number><foreign-keys><key app="EN" db-id="v22aw5p0kf5fpve0sr8xxreie02sxs9z202x" timestamp="1528402134">958</key></foreign-keys><ref-type name="Web Page">12</ref-type><contributors><authors><author>UDAQ</author></authors></contributors><titles><title>Uinta Basin: 2014 Air Agencies Oil and Gas Emissions Inventory</title></titles><volume>2018</volume><number>1 June 2018</number><dates><year>2018</year></dates><pub-location>Salt Lake City, Utah</pub-location><urls><related-urls><url>https://deq.utah.gov/legacy/destinations/u/uintah-basin/air-agencies-emissions-inventory/index.htm</url></related-urls></urls></record></Cite></EndNote>]. Wells constructed after 2014 are excluded from these analyses.

Commented [CKB18]: Why?

Well Pad Property	Aerial Survey		Ground Surveys A&B	
	Entire Population	Emissions Detected	Entire Population	Emissions Detected
% that were oil wells	41.6%	75.0%	63.7%	62.8%
Avg. oil production (bbl day <sup>-1</sup> )	6.7 ± 0.7	41.2 ± 29.4	12.3 ± 3.6	18.2 ± 6.5
Avg. gas production (MCF day <sup>-1</sup> )	100.1 ± 8.1	162.3 ± 93.9	84.2 ± 27.6	94.3 ± 50.0
Avg. pad age (months)	159 ± 4	107 ± 67	153.6 ± 12.7	141.6 ± 23.1
Avg. wells per pad	1.4 ± 0.0	1.6 ± .6	1.3 ± 0.1	1.3 ± 0.2
% with glycol dehydrators <sup>a</sup>	14.2%	22.2%	26.5%	14.3%
% with emission controls on tanks <sup>a</sup>	13.3%	55.6%	26.5%	40.0%
Avg. number of tanks per pad <sup>a</sup>	2.6 ± 0.1	4.7 ± 4.6	2.7 ± 0.2	3.4 ± 0.4

Many of the properties associated with an increase in detectable emissions were correlated. In the population of wells included in the aerial survey, per-pad production of barrels of oil equivalent (bbl day<sup>-1</sup> of oil + MCF day<sup>-1</sup> of gas / 5.8) was negatively correlated with pad age ( $r^2 = 0.21$ ;  $p = 0.04$ ) when production was binned by pad age at 24-month intervals. When binned in the same way, being an oil well pad (oil well pads were given a value of 1 and gas well pads a value of 0) was also negatively correlated with pad age ( $r^2 = 0.15$ ;  $p = 0.08$ ), probably because recent commodity prices have made oil production more cost-competitive than gas production. Younger, higher-producing pads may have more detectable emissions because equipment, including liquid storage tanks, is subject to higher throughput and higher pressures at these pads relative to lower-producing pads. The number of emission plumes detected per pad in the surveyed dataset was not significantly correlated with pad age ( $r^2 = 0.12$ ;  $p = 0.12$ ), but was correlated with production of barrels of oil equivalent ( $r^2 = 0.75$ ;  $p < 0.01$ ) and with being an oil well pad ( $r^2 = 0.26$ ;  $p = 0.02$ ).

Pads with emissions controls on liquid storage tanks were more likely to have emissions that were detectable from the helicopter. Having tank emissions controls was correlated with production of

barrels of oil equivalent in the same binned dataset ( $r^2 = 0.39$ ;  $p < 0.01$ ). Also, the 2016 STEPP ground-based survey that only included wells with tank emissions controls showed that 39% of the wells surveyed had detectable emissions and that 82% of detected emissions were from tanks and infrastructure connected to tanks [ ADDIN EN.CITE

<EndNote><Cite><Author>Mansfield</Author><Year>2017</Year><RecNum>965</RecNum><DisplayText>(Mansfield et al., 2017)</DisplayText><record><rec-number>965</rec-number><foreign-keys><key app="EN" db-id="v22aw5p0kf5fpve0sr8xxreie02sxs9z202x" timestamp="1531948429">965</key></foreign-keys><ref-type name="Report">27</ref-type><contributors><authors><author>Mansfield, M. L.</author><author>Lyman, S. N.</author><author>O'Neil, Trevor</author><author>Anderson, Randy</author><author>Jones, C.</author><author>Tran, H.</author><author>Mathis, J.</author><author>Barickman, P.</author><author>Oswald, W.</author><author>LeBaron, B.</author></authors></contributors><titles><title>Storage Tank Emissions Pilot Project (STEPP): Fugitive Organic Compound Emissions from Liquid Storage Tanks in the Uinta Basin</title></titles><dates><year>2017</year></dates><pub-location>Vernal, Utah</pub-location><publisher>Utah State University</publisher><urls><related-urls><uri>https://documents.deq.utah.gov/air-quality/planning/technical-analysis/DAQ-2017-009061.pdf</uri></related-urls></record></Cite></EndNote>]. [ ADDIN EN.CITE

**Commented [CKB19]:** Terminology – this means tanks (pressure relief devices and tank piping)

<EndNote><Cite>AuthorYear="1"><Author>Brantley</Author><Year>2015</Year><RecNum>978</RecNum><DisplayText>(Brantley et al., 2015)</DisplayText><record><rec-number>978</rec-number><foreign-keys><key app="EN" db-id="v22aw5p0kf5fpve0sr8xxreie02sxs9z202x" timestamp="1532616237">978</key></foreign-keys><ref-type name="Journal Article">17</ref-type><contributors><authors><author>Brantley, Halley L</author><author>Thoma, Eben D</author><author>Eisele, Adam P</author></authors></contributors><titles><title>Assessment of volatile organic compound and hazardous air pollutant emissions from oil and natural gas well pads using mobile remote and on-site direct measurements</title><secondary-title>Journal of the Air & Waste Management Association</secondary-title></titles><periodical><full-title>Journal of the Air & Waste Management Association</full-title><abbr-1>J. Air Waste Manage. Assoc.</abbr-1><abbr-2>J Air Waste Manage Assoc</abbr-2></periodical><pages>1072-1082</pages><volume>65</volume><number>9</number><dates><year>2015</year></dates><isbn>1 096-2247</isbn></urls></record></Cite></EndNote>] came to a similar conclusion for well pads at which they measured emissions throughout the Rocky Mountain region. Tanks with emissions controls often leak, leading to detectable emission plumes.

The Ground Survey A&B results showed similar trends, with pads at which emissions were detected being younger, with higher oil and gas production, more tanks per pad, and more likely to have tank emissions controls. The differences between the entire surveyed population (Aerial and Ground Surveys A&B) and the pads with detected emissions were smaller in Ground Surveys A&B the ground survey than in the Aerial Survey, however. We expect that this was due to the large difference in the minimum detectable leak rates between the aerial and ground surveys. Only very large emission plumes were detectable in the aerial survey, so differences between pads with detectable plumes and all surveyed pads were more pronounced.

### 3.6. Qualitative Plume Size

[ REF\_Ref524012587 \h ] shows the prevalence of qualitative size classes of emission plumes detected in the ground survey and during the STEPP study [ ADDIN EN.CITE <EndNote><Cite><Author>Mansfield</Author><Year>2017</Year><RecNum>965</RecNum><DisplayText>(Mansfield et al., 2017)</DisplayText><record><rec-number>965</rec-number><foreign-keys><key app="EN" db-id="v22aw5p0kf5fpve0sr8xxreie02sxs9z202x" timestamp="1531948429">965</key></foreign-keys><ref-type name="Report">27</ref-type><contributors><authors><author>Mansfield, M. L.</author><author>Lyman, S. N.</author><author>O'Neil, Trevor</author><author>Anderson, Randy</author><author>Jones, C.</author><author>Tran, H.</author><author>Mathis, J.</author><author>Barickman, P.</author><author>Oswald, W.</author><author>LeBaron, B.</author></authors></contributors><titles><title>Storage Tank Emissions Pilot Project (STEPP): Fugitive Organic Compound Emissions from Liquid Storage Tanks in the Uinta Basin</title></titles><dates><year>2017</year></dates><pub-location>Vernal, Utah</pub-location><publisher>Utah State University</publisher><urls><related-urls><url>https://documents.deq.utah.gov/air-quality/planning/technical-analysis/DAQ-2017-009061.pdf</url></related-urls></urls></record></Cite></EndNote>]. In the whole dataset, most emissions were categorized as small or medium, but for well pads with emissions controls on tanks, medium and large plumes were more common, and the percentages were similar to what was found in the STEPP study. This could be caused by the fact that pads with controlled tanks are more likely to have high oil and gas production, so emissions from tanks tend to be larger when they do occur.

**Table [ STYLEREF 1 \s ]-[ SEQ Table \\* ARABIC \s 1 ]. Prevalence of plumes of different qualitative size categories in the entire Ground Survey A&B dataset, for well pads with controlled tanks, and for the STEPP study (which only included pads with controlled tanks).**

Plume size	Ground Surveys A&B Entire dataset (419 pads)		Ground Surveys A&B Pads with controlled tanks (133 pads)		STEPP study (?? Pads)	
Small	75	38%	27	28%	46	23%
Medium	77	39%	34	36%	74	38%
Large	44	22%	34	36%	76	39%
TOTAL	196	100%	95	100%	196	100%

[ REF\_Ref524012603 \h ] demonstrates a relationship between the ability to perceive a plume and the observation distance. We performed this analysis on the whole dataset only because the existence of controlled tanks does not affect the tested relationship. Similar to findings from the STEPP study, the fraction of well pads with no observable emissions increased from about 40% to almost 70% as the observation distance increased, and the fraction of small and medium plumes decreased. All plumes detected at distances over 103 m were in the large-size class. Distance from the emission source has been shown in other studies to be inversely related to detection limits [ ADDIN EN.CITE <EndNote><Cite><Author>Ravikumar</Author><Year>2016</Year><RecNum>981</RecNum><DisplayText>(Ravikumar et al., 2016)</DisplayText><record><rec-number>981</rec-number><foreign-keys><key app="EN" db-id="v22aw5p0kf5fpve0sr8xxreie02sxs9z202x" timestamp="1532618364">981</key></foreign-keys><ref-type name="Journal Article">17</ref-type><contributors><authors><author>Ravikumar, Arvind P</author><author>Wang,


Jingfan</author><author>Brandt, Adam R</author></authors></contributors><titles><title>Are optical gas imaging technologies effective for methane leak detection?</title><secondary-title>Environmental Science & Technology</secondary-title></titles><periodical><full-title>Environmental Science & Technology</full-title><abbr-1>Environ. Sci. Technol.</abbr-1><abbr-2>Environ Sci Technol</abbr-2></periodical><pages>718-724</pages><volume>51</volume><number>1</number><dates><year>2016</year></dates><isbn>0013-936X</isbn><urls></urls></record></Cite></EndNote>].

**Table [ STYLEREf 1 \s ]-[ SEQ Table \\* ARABIC \s 1 ]. Relationship between observation distance and qualitative size of plumes for the Ground Survey A&B dataset.**

N, S, M, L are no detectable emissions, small, medium and large emissions, respectively.

Distance range	Pads of each size (N,S,M,L)	Percentage (N,S,M,L)
less than 16 m	7, 6, 1, 3	41%, 35%, 6%, 18%
16 to 34 m	45, 15, 28, 10	46%, 15%, 29%, 10%
34 to 57 m	120, 31, 20, 11	66%, 17%, 11%, 6%
57 to 80 m	77, 20, 18, 11	61%, 16%, 14%, 9%
80 to 103 m	32, 3, 10, 7	62%, 6%, 19%, 13%
103 to 126 m	6, 0, 0, 1	86%, 0%, 0%, 14%
over 126 m	2, 0, 0, 1	67%, 0%, 0%, 33%

For the Ground Survey A&B entire dataset, oil well pads with qualitatively large plumes had more oil production than well pads with other size classifications ([ REF \_Ref524015180 \h ]). This same correlation was seen in a subset of oil well pads with emissions controls on tanks. This trend was slightly different from the STEPP study, in which pads with highest oil production were associated with both medium plumes and large plumes. In contrast, gas well pads with no detected emissions had higher gas production than pads with small, medium and large emission plumes ([ REF \_Ref524015181 \h ]).



**Figure [ STYLEREf 1 \s ]-[ SEQ Figure \\* ARABIC \s 1 ]. February 2018 oil production versus qualitative emission plume size, for the entire Ground Survey A&B dataset and for pads with controlled tanks.**

Non indicates no detected emissions. Whiskers represent 90% confidence intervals.




Figure [ STYLEREf 1 \s ]-[ SEQ Figure \\* ARABIC \s 1 ]. February 2018 natural gas production versus qualitative emission plume size.

Non indicates no detected emissions. Whiskers represent 90% confidence intervals.

### 3.7. Results by Company

[ REF \_Ref524012465 \h ] and [ REF \_Ref524073833 \h ] provide company-level information about the results of the Aerial and Ground Surveys A&B. The company with the highest percentage of pads in the aerial survey with detectable emissions (company B) had the fifth-highest detectable emissions in the ground survey, and several companies with no detectable emissions in the aerial survey had a detection rate of 20% or more in the ground survey ([ REF \_Ref524012465 \h ]). These discrepancies were likely caused by the different detection limits and population sizes of the two surveys.

Table [ STYLEREf 1 \s ]-[ SEQ Table \\* ARABIC \s 1 ]. Aerial and Ground Survey A&B results, organized by company.



# Utah State University

BINGHAM RESEARCH CENTER

Total pads is the number of pads surveyed, and detects is the number of surveyed pads at which at least one emission plume was detected. Response received indicates whether the company responded to our request for information about observed emissions.

Company ID	Aerial Survey			Ground Surveys A&B			% Oil wells in survey	Response received?
	Total pads	Detects	Percent detects	Total pads	Detects	Percent detects		
A	16	0	0.0%	16	8	50%	81%	No
B	121	6	5.0%	64	19	30%	95%	Yes
C	58	0	0.0%	0			47%	N/A
D	21	0	0.0%	13	3	23%	100%	No
E	227	2	0.9%	58	28	48%	71%	Yes
F	474	1	0.2%	111	21	19%	71%	Yes
G	581	0	0.0%	85	36	42%	19%	Yes
H	755	2	0.3%	30	6	20%	30%	Yes
I	7	0	0.0%	4	1	25%	100%	No
J	65	1	1.5%	1	1	100%	91%	Yes
K	248	2	0.8%	35	5	14%	2%	Yes
L	75	2	2.7%	2	1	50%	69%	No
M	257	0	0.0%	0			23%	N/A
N	1	0	0.0%	0			0%	N/A
O	24	0	0.0%	0			0%	N/A
P	273	0	0.0%	0			69%	N/A
Q	2	0	0.0%	0			100%	N/A
R	1	0	0.0%	0			100%	N/A
S	13	0	0.0%	0			8%	N/A
T	6	0	0.0%	0			0%	N/A
<b>TOTALS</b>	<b>3225</b>	<b>16</b>	<b>0.5%</b>	<b>419</b>	<b>129</b>	<b>31%</b>	<b>42%</b>	<b>7 out of 11</b>

Commented [CKB20]: I thought total was 3,428?

The frequency and qualitative size of detected emission plumes varied widely among companies whose well pads were surveyed in this study ([ REF \_Ref524073833 \h ]). For the entire dataset, company B was statistically significantly associated with larger emission plumes than other companies, and companies E and G had significantly higher numbers of plumes detected per pad. For several companies (B, E, G, and H), the frequency and severity of detected emissions were higher for the subset of wells with tank emissions controls. Severity scores tended to be similar across this study and STEPP, except for company F, which had a much lower severity score in this study. The number of plumes detected per pad was higher for three out of five companies in this study compared to STEPP. This could be due to the increased number of detected plumes that were categorized as small in this study relative to STEPP ([ REF \_Ref524012587 \h ]). Company K had the lowest number of plumes per pad and the lowest severity score. Company F, which had the largest number of surveyed pads in this study, also had significantly lower values for both metrics and had much lower values than during the STEPP study. In the STEPP study, responses from operators were received for 27% (48 of 178) of observed plumes.

All operators that responded to the survey reported that they had a leak detection and repair program for wells in the Uinta Basin, though some reported that not all of their wells were covered by the program ([ REF \_Ref524073833 \h ]). Of the companies that reported an inspection frequency, two reported that they conducted semiannual inspections, one reported annual inspections, and one reported that some of their wells were inspected annually, while others were inspected monthly. No clear relationship existed between inspection frequency and emission frequency or severity in [ REF \_Ref524073833 \h ].

Pads with emissions controls on tanks had a higher number of detected plumes per pad and a worse severity score than the entire dataset, and this difference was statistically significant (see the last row of [ REF \_Ref524073833 \h ]). This is similar to the findings demonstrated in [ REF \_Ref524013169 \h ], [ REF \_Ref524088163 \h ], and [ REF \_Ref524012587 \h ], and together these findings show that wells pads with emission controls on tanks are more likely to (1) have detectable emissions from tanks and (2) have qualitatively larger emission plumes than the dataset as a whole.

**Table [ STYLEREf 1 \s ]-[ SEQ Table \\* ARABIC \s 1 ]. Average frequency and qualitative severity of detected emission plumes by company.**

Values in blue indicate that the company's performance for a given metric is better than the group, as determined by a Monte Carlo analysis of statistical significance, and values in red indicate that a company underperformed the group

. LDAR frequency is also shown and indicates the frequency at which companies reported they inspect for leaks at the well pads in the survey.

Company	LDAR frequency	Ground Surveys A&B - Entire dataset		Ground Surveys A&B - Pads with controlled tanks		STEPP study	
		Plumes per pad	Severity score	Plumes per pad	Severity score	Plumes per pad	Severity score
A	--	0.63	2.5	0.83	2.4	0.27	2.2
B	Semiannual/none	0.41	2.2	0.44	2.4	0.36	2.4
C	--	--	--	--	--	0.36	2.2
D	--	0.31	2.3	0.36	2.3	0.38	2.6
E	None	0.91	1.9	1.47	2	0.55	1.8
F	Semiannual	0.3	1.6	0.13	1	0.6	2.2
G	Annual	0.66	1.7	1.43	1.8	--	--
H	Annual/monthly	0.2	2	0.25	2.3	--	--
I	--	0.25	2	0.33	2	--	--
J	Semiannual	1	2	1	2	--	--
K	--	0.17	1	0	0	--	--
L	--	1	1	1	1	--	--
Average		0.47	1.8	0.72	1.9	0.4	2.2

### 3.8. Reported Repairs

Companies reported that they made repairs in response to this study at 56 well pads (43% of all pads with observed emissions). At 34% of the pads for which we received responses, companies indicated

**Commented [CKB21]:** With tank controls? Without tank controls? A mix?

that observed emissions from tanks were part of normal operations, and thus repairs were not needed. Repairs were completed within  $43 \pm 9$  days of the ground survey date. [ REF \_Ref524167480 \h ] shows repair categories, the number of repairs made, and costs incurred for repairs.

**Commented [CKB22]:** How is the uncertainty estimated? Is 43 days an average? Median?

**Table [ STYLEREf 1 \s ]-[ SEQ Table \\* ARABIC \s 1 ]. Number and cost of repairs reported by operators.**

Repair category	Number of repairs made	Cost of repairs
Hatch maintenance	26	\$308 $\pm$ 122
Piping repair	8	\$127 $\pm$ 116
Combustor maintenance	7	\$119 $\pm$ 130
Pressure relief valve repair	7	--
Hatch replacement	6	\$3,872 $\pm$ \$1,630
Regulator replacement	1	--

### 3.9. Comparison of Regulatory Jurisdictions

The majority of the Uinta Basin is Indian country, which includes the Uintah and Ouray Indian Reservation and other lands for which the Ute Indian Tribe and the U.S. Environmental Protection Agency have regulatory authority for air quality. The state of Utah has regulatory authority for air quality on land that does not fall within Indian country. [ REF \_Ref524085189 \h ] shows the survey results and well pad properties for Indian country and lands under state jurisdiction for air quality.

[ REF \_Ref524085189 \h ] shows that emissions were four times more likely to be detected at well pads under state air quality jurisdiction during the aerial survey. In contrast, emissions were slightly more likely to be detected at pads in Indian country during the ground survey. As mentioned in the previous section, the detection limit for the aerial survey was much higher than for the ground survey, so only very large emission plumes were detected. Pads on state jurisdiction were more likely to be oil wells, had higher production, and were younger (in the aerial survey), all characteristics associated with a greater likelihood of having detectable emissions. For the ground survey, the much lower detection limit meant that emissions from low-producing and high-producing wells were both detectable, and the differences in well properties across regulatory jurisdictions were less important.

Table [ STYLEREf 1 \s ]-[ SEQ Table \\* ARABIC \s 1 ]. Comparison of survey results and pad properties for different areas of jurisdiction for air quality regulations in the Uinta Basin. Data are for all surveyed pads unless otherwise indicated. (a) indicates data taken from the 2014 Utah air agencies oil and gas emissions inventory [ ADDIN EN.CITE <EndNote><Cite><Author>UDAQ</Author><Year>2018</Year><RecNum>958</RecNum><DisplayText>(UDAQ, 2018)</DisplayText><record><rec-number>958</rec-number><foreign-keys><key app="EN" db-id="v22aw5p0kf5fpve0sr8xxreie02sxs9z202x" timestamp="1528402134">958</key></foreign-keys><ref-type name="Web Page">12</ref-type><contributors><authors><author>UDAQ</author></authors></contributors><titles><title>Uinta Basin: 2014 Air Agencies Oil and Gas Emissions Inventory</title></titles><volume>2018</volume><number>1 June 2018</number><dates><year>2018</year></dates><pub-location>Salt Lake City, Utah</pub-location><urls><related-urls><url>https://deq.utah.gov/legacy/destinations/u/uintah-basin/air-agencies-emissions-inventory/index.htm</url></related-urls></urls></record></Cite></EndNote>]. Wells constructed after 2014 are excluded from these analyses.

	Aerial Survey		Ground Survey <sup>A&amp;B</sup>	
	State of Utah	Indian Country	State of Utah	Indian Country
% of all surveyed pads	17.7%	82.3%	43.7%	56.3%
Percent of pads with detects	1.2%	0.3%	26.2%	31.8%
% that were oil wells	99.5%	29.1%	98.9%	36.4%
Avg. oil production (bbl day <sup>-1</sup> )	18.3 ± 3.2	4.2 ± 0.5	20.7 ± 5.5	5.8 ± 4.8
Avg. gas production (MCF day <sup>-1</sup> )	56.3 ± 18.8	109.7 ± 19.3	86.0 ± 41.8	82.9 ± 36.8
Avg. pad age (months)	112 ± 9	169 ± 10	157.2 ± 19.3	150.7 ± 17.0
Avg. wells per pad	1.1 ± 0.0	1.5 ± 0.0	1.1 ± 0.1	1.4 ± 0.1
% with glycol dehydrators <sup>a</sup>	0.0%	15.3%	0.0%	46.7%
% with tank emission controls <sup>a</sup>	44.6%	10.9%	50.9%	8.0%
Avg. number of tanks per pad <sup>a</sup>	3.3 ± 0.1	2.6 ± 0.2	3.4 ± 0.3	2.3 ± 0.3

### 3.10. Comparison of Aerial Survey Results with Lyon et al. Study

Emission plumes were detected at a much lower percentage of oil and gas facilities in the current study relative to the Uinta Basin portion of the study performed by [ ADDIN EN.CITE <EndNote><Cite AuthorYear="1"><Author>Lyon</Author><Year>2016</Year><RecNum>700</RecNum><DisplayText>(Lyon et al., 2016)</DisplayText><record><rec-number>700</rec-number><foreign-keys><key app="EN" db-id="v22aw5p0kf5fpve0sr8xxreie02sxs9z202x" timestamp="1472841023">700</key></foreign-keys><ref-type name="Journal Article">17</ref-type><contributors><authors><author>Lyon, David R</author><author>Alvarez, Ramón A</author><author>Zavala-Araiza, Daniel</author><author>Brandt, Adam R</author><author>Jackson, Robert B</author><author>Hamburg, Steven P</author></authors></contributors><titles><title>Aerial surveys of elevated hydrocarbon emissions from oil and gas production sites</title><secondary-

# UtahStateUniversity

BINGHAM RESEARCH CENTER

title>Environmental science & technology</secondary-title></titles><periodical><full-  
title>Environmental Science & Technology</full-title><abbr-1>Environ. Sci. Technol.</abbr-  
1><abbr-2>Environ Sci Technol</abbr-2></periodical><pages>4877-  
4886</pages><volume>50</volume><number>9</number><dates><year>2016</year></dates><isbn>0  
013-936X</isbn><urls></urls></record></Cite></EndNote>] ([ REF \_Ref524088636 \h ]). The surveyed  
well pad population in this study was older, produced less oil, and produced a lower percentage of its  
energy from oil (determined using the method presented by [ ADDIN EN.CITE <EndNote><Cite  
AuthorYear="1"><Author>Lyon</Author><Year>2016</Year><RecNum>700</RecNum><DisplayText>(L  
yon et al., 2016)</DisplayText><record><rec-number>700</rec-number><foreign-keys><key app="EN"  
db-id="v22aw5p0kf5fpve0sr8xxreie02sxs9z202x" timestamp="1472841023">700</key></foreign-  
keys><ref-type name="Journal Article">17</ref-type><contributors><authors><author>Lyon, David  
R</author><author>Alvarez, Ramón A</author><author>Zavala-Araiza,  
Daniel</author><author>Brandt, Adam R</author><author>Jackson, Robert  
B</author><author>Hamburg, Steven P</author></authors></contributors><titles><title>Aerial surveys  
of elevated hydrocarbon emissions from oil and gas production sites</title><secondary-  
title>Environmental science & technology</secondary-title></titles><periodical><full-  
title>Environmental Science & Technology</full-title><abbr-1>Environ. Sci. Technol.</abbr-  
1><abbr-2>Environ Sci Technol</abbr-2></periodical><pages>4877-  
4886</pages><volume>50</volume><number>9</number><dates><year>2016</year></dates><isbn>0  
013-936X</isbn><urls></urls></record></Cite></EndNote>]) relative to the survey conducted by Lyon  
et al., all properties associated with a decreased likelihood of emissions that were detectable from the  
helicopter.




Figure [ STYLEREF 1 \s ]-[ SEQ Figure \\* ARABIC \s 1 ]. Comparison of well pad properties from the [ ADDIN EN.CITE <EndNote><Cite AuthorYear="1"><Author>Lyon</Author><Year>2016</Year><RecNum>700</RecNum><DisplayText>(Lyon et al., 2016)</DisplayText><record><rec-number>700</rec-number><foreign-keys><key app="EN" db-id="v22aw5p0kf5fpve0sr8xxreie02sxs9z202x" timestamp="1472841023">700</key></foreign-keys><ref-type name="Journal Article">17</ref-type><contributors><authors><author>Lyon, David R</author><author>Alvarez, Ramón A</author><author>Zavala-Araiza, Daniel</author><author>Brandt, Adam R</author><author>Jackson, Robert B</author><author>Hamburg, Steven P</author></authors></contributors><titles><title>Aerial surveys of elevated hydrocarbon emissions from oil and gas production sites</title><secondary-title>Environmental science & technology</secondary-title></titles><periodical><full-title>Environmental Science & Technology</full-title><abbr-1>Environ. Sci. Technol.</abbr-1><abbr-2>Environ Sci Technol</abbr-2></periodical><pages>4877-4886</pages><volume>50</volume><number>9</number><dates><year>2016</year></dates><isbn>0013-936X</isbn></urls></record></Cite></EndNote>] with this [Aerial Survey study](#).

The panels show (clockwise from top left) percent of pads surveyed with emissions detected from the helicopter, age of all surveyed pads, oil production of surveyed pads, and percent energy from oil of surveyed

pads. Top of bars are averages, and whiskers represent 95% confidence intervals. Confidence intervals for percent of pads with detected emissions are derived from daily values.

Englander et al. [ ADDIN EN.CITE <EndNote><Cite  
ExcludeAuth="1"><Author>Englander</Author><Year>2018</Year><RecNum>987</RecNum><DisplayText>(2018)</DisplayText><record><rec-number>987</rec-number><foreign-keys><key app="EN" db-id="v22aw5p0kf5fpve0sr8xxreie02sxs9z202x" timestamp="1534361959">987</key></foreign-keys><ref-type name="Journal Article">17</ref-type><contributors><authors><author>Englander, Jacob G</author><author>Brandt, Adam R</author><author>Conley, Stephen</author><author>Lyon, David R</author><author>Jackson, Robert B</author></authors></contributors><titles><title>Aerial inter-year comparison and quantification of methane emissions persistence in the Bakken formation of North Dakota, USA</title><secondary-title>Environmental science & technology</secondary-title></titles><periodical><full-title>Environmental Science & Technology</full-title><abbr-1>Environ. Sci. Technol.</abbr-1><abbr-2>Environ Sci Technol</abbr-2></periodical><dates><year>2018</year></dates><isbn>0013-936X</isbn><urls></urls></record></Cite></EndNote>] returned to the Bakken oil field in North Dakota and conducted an aerial infrared camera survey one year after the survey conducted by Lyon et al. [ ADDIN EN.CITE <EndNote><Cite  
ExcludeAuth="1"><Author>Lyon</Author><Year>2016</Year><RecNum>700</RecNum><DisplayText>(2016)</DisplayText><record><rec-number>700</rec-number><foreign-keys><key app="EN" db-id="v22aw5p0kf5fpve0sr8xxreie02sxs9z202x" timestamp="1472841023">700</key></foreign-keys><ref-type name="Journal Article">17</ref-type><contributors><authors><author>Lyon, David R</author><author>Alvarez, Ramón A</author><author>Zavala-Araiza, Daniel</author><author>Brandt, Adam R</author><author>Jackson, Robert B</author><author>Hamburg, Steven P</author></authors></contributors><titles><title>Aerial surveys of elevated hydrocarbon emissions from oil and gas production sites</title><secondary-title>Environmental science & technology</secondary-title></titles><periodical><full-title>Environmental Science & Technology</full-title><abbr-1>Environ. Sci. Technol.</abbr-1><abbr-2>Environ Sci Technol</abbr-2></periodical><pages>4877-4886</pages><volume>50</volume><number>9</number><dates><year>2016</year></dates><isbn>0013-936X</isbn><urls></urls></record></Cite></EndNote>]. Both surveys were conducted in September. For pads that were surveyed in both years, Englander et al. found a similar percentage of detected leaks (11.1% versus 10.8%). Further, they showed that pads with detected emissions in the first study were likely to be emitting in the second study. We, on the other hand, did not detect emissions at any of the 652 pads in our survey that were also part of the Lyon et al. survey, even though Lyon et al. detected emissions at 47 (7%) of those pads. Unlike the Englander et al. study, our study occurred four years after the original Lyon et al. study, allowing for significant changes in the industry to occur (e.g., [ REF\_Ref524088636 \h ]), and in a different season, resulting in poorer detection limits (see discussion below).

Wind speed and cloudiness were similar during this study and the Uinta Basin portion of the Lyon et al. study ([ REF\_Ref524088664 \h ]). Snow cover was not present when the Lyon et al. study was conducted but was very low during this study as well. The most significant meteorological difference between the two studies was temperature.




Figure [ STYLERE 1 \s ]-[ SEQ Figure \\* ARABIC \s 1 ]. Comparison of meteorological conditions during the [ ADDIN EN.CITE <EndNote><Cite AuthorYear="1"><Author>Lyon</Author><Year>2016</Year><RecNum>700</RecNum><DisplayText>{Lyon et al., 2016}</DisplayText><record><rec-number>700</rec-number><foreign-keys><key app="EN" db-id="v22aw5p0kf5fpve0sr8xxreie02sxs9z202x" timestamp="1472841023">700</key></foreign-keys><ref-type name="Journal Article">17</ref-type><contributors><authors><author>Lyon, David R</author><author>Alvarez, Ramón A</author><author>Zavala-Araiza, Daniel</author><author>Brandt, Adam R</author><author>Jackson, Robert B</author><author>Hamburg, Steven P</author></authors></contributors><titles><title>Aerial surveys of elevated hydrocarbon emissions from oil and gas production sites</title><secondary-title>Environmental science & technology</secondary-title></titles><periodical><full-title>Environmental Science & Technology</full-title><abbr-1>Environ. Sci. Technol.</abbr-1><abbr-2>Environ Sci Technol</abbr-2></periodical><pages>4877-4886</pages><volume>50</volume><number>9</number><dates><year>2016</year></dates><isbn>0013-936X</isbn></urls></record></Cite></EndNote>] survey and this study.



The panels show (clockwise from top left) ambient temperature, percent snow cover, wind speed, and percent of survey hours that were cloud-free. Top of bars are averages, and whiskers represent 95% confidence intervals.

Lower temperature is associated with poorer detection with infrared leak detection cameras [ ADDIN EN.CITE

<EndNote><Cite><Author>Ravikumar</Author><Year>2017</Year><RecNum>982</RecNum><DisplayText>{Ravikumar and Brandt, 2017; Ravikumar et al., 2016}</DisplayText><record><rec-number>982</rec-number><foreign-keys><key app="EN" db-id="v22aw5p0kf5fpve0sr8xxreie02sxs9z202x" timestamp="1532619316">982</key></foreign-keys><ref-type name="Journal Article">17</ref-type><contributors><authors><author>Ravikumar, Arvind P</author><author>Brandt, Adam R</author></authors></contributors><titles><title>Designing better methane mitigation policies: the challenge of distributed small sources in the natural gas sector</title><secondary-title>Environmental Research Letters</secondary-title></titles><periodical><full-title>Environmental Research Letters</full-title></periodical><pages>044023</pages><volume>12</volume><number>4</number><dates><year>2017</year></dates><isbn>1748-9326</isbn><urls></urls></record></Cite><Cite><Author>Ravikumar</Author><Year>2016</Year><RecNum>981</RecNum><record><rec-number>981</rec-number><foreign-keys><key app="EN" db-id="v22aw5p0kf5fpve0sr8xxreie02sxs9z202x" timestamp="1532618364">981</key></foreign-keys><ref-type name="Journal Article">17</ref-type><contributors><authors><author>Ravikumar, Arvind P</author><author>Wang, Jingfan</author><author>Brandt, Adam R</author></authors></contributors><titles><title>Are optical gas imaging technologies effective for methane leak detection?</title><secondary-title>Environmental Science & Technology</secondary-title></titles><periodical><full-title>Environmental Science & Technology</full-title><abbr-1>Environ. Sci. Technol.</abbr-1><abbr-2>Environ Sci Technol</abbr-2></periodical><pages>718-724</pages><volume>51</volume><number>1</number><dates><year>2016</year></dates><isbn>0013-936X</isbn><urls></urls></record></Cite></EndNote>], and this could account for much of the difference in detection between the two studies. We used the Ravikumar model of plume detectability by infrared leak detection cameras to explore the extent to which meteorological conditions may have impacted the results of the two studies. For the aerial survey, the background behind the plume was always the ground, so the detection limit was determined by the contrast between the apparent plume temperature (a measure of the amount of infrared energy emitted by and reflected from the plume in the camera's bandwidth of 3.2 to 3.4  $\mu\text{m}$ ) and the apparent ground temperature (a measure of ... heat loss from earth plus solar reflection).

[ REF\_Ref524088682 \h ] shows the relationship between the modeled minimum detection limits of the infrared camera and the apparent ground temperature for the meteorological conditions of the two studies. The simulated detection limit was poorest at an apparent ground temperature of about 10°C above the actual ambient temperature. Since the apparent ground temperature was not recorded during the studies, it is impossible to know the actual detection limits with certainty. If we assume the apparent ground temperature was 20 degrees above the ambient air temperature, the methane detection limits for the Lyon et al. study and this study would be about 1 and 4 g s<sup>-1</sup>, respectively.

**Commented [CKB23]:** Can apparent temperature be measured? Should we recommend that in future IR survey work include measuring it?




Figure 1. Relationship between apparent ground temperature and the minimum detection limit for methane

, as calculated using the Ravikumar model.

Whiskers represent 95% confidence intervals. The orange vertical lines represent average daytime ambient air temperature.

Controlled hydrocarbon releases provide another way to compare detection limits in the two studies. In this study, the propane plume was marginally detectable somewhere between 1.89 and 5.04 g s<sup>-1</sup>. Lyon et al. [ ADDIN EN.CITE <EndNote><Cite

ExcludeAuth="1"><Author>Lyon</Author><Year>2016</Year><RecNum>700</RecNum><DisplayText>(2016)</DisplayText><record><rec-number>700</rec-number><foreign-keys><key app="EN" db-id="v22aw5p0kf5fpve0sr8xxreie02sxs9z202x" timestamp="1472841023">700</key></foreign-keys><ref-type name="Journal Article">17</ref-type><contributors><authors><author>Lyon, David R</author><author>Alvarez, Ramón A</author><author>Zavala-Araiza, Daniel</author><author>Brandt, Adam R</author><author>Jackson, Robert B</author><author>Hamburg, Steven P</author></authors></contributors><titles><title>Aerial surveys of elevated hydrocarbon emissions from oil and gas production sites</title><secondary-title>Environmental science & technology</secondary-title></titles><periodical><full-title>Environmental Science & Technology</full-title><abbr-1>Environ. Sci. Technol.</abbr-1><abbr-2>Environ Sci Technol</abbr-2></periodical><pages>4877-4886</pages><volume>50</volume><number>9</number><dates><year>2016</year></dates><isbn>0013-936X</isbn></urls></record></Cite></EndNote>] reported that a methane emission plume of 3 g s<sup>-1</sup> was marginally detectable. Infrared camera detection limits for propane are about four times lower (i.e., better) than for methane, so we can assume a methane detection limit in our study in the range of 8 to 20 g s<sup>-1</sup>, between 2.5 and 7 times worse than the detection limits reported by Lyon et al.

[ REF\_Ref524088694 \h ] presents the percent of surveyed well pads with detected emissions, in this work and in Lyon et al., plotted against pad age, the percentage of energy produced at the pad that was from oil, oil production, and gas production. Lyon et al. [ ADDIN EN.CITE <EndNote><Cite

ExcludeAuth="1"><Author>Lyon</Author><Year>2016</Year><RecNum>700</RecNum><DisplayText>(

2016) record=700 foreign-keys=<key app="EN" db-id="v22aw5p0kf5fpve0sr8xxreie02sxs9z202x" timestamp="1472841023">700/key> ref-type name="Journal Article">17/ref-type> contributors=<authors>author>Lyon, David R</author>author>Alvarez, Ramón A</author>author>Zavala-Araiza, Daniel</author>author>Brandt, Adam R</author>author>Jackson, Robert B</author>author>Hamburg, Steven P</author>/authors> titles=<title>Aerial surveys of elevated hydrocarbon emissions from oil and gas production sites</title>secondary-title>Environmental science & technology</secondary-title>/titles> periodical=<full-title>Environmental Science & Technology</full-title>abbr-1>Environ. Sci. Technol.</abbr-1>abbr-2>Environ Sci Technol</abbr-2>/periodical> pages>4877-4886</pages>volume>50</volume>number>9</number>dates=<year>2016</year>/dates> isbn>0 013-936X</isbn>urls>/urls> record=<Cite></EndNote>] plotted these same parameters in their paper in the same way, but for their nationwide dataset, while we only plot Uinta Basin data here. The same general trends can be seen in both studies, with more detected emissions from newer wells, oil wells, and higher-producing wells.




Figure 1. Percent of pads with detected emissions versus well properties, in this Aerial Survey work and [ ADDIN EN.CITE <EndNote>Cite AuthorYear="1">Author>Lyon</Author><Year>2016</Year><RecNum>700</RecNum><DisplayText>(Lyon et al., 2016)</DisplayText>record=<rec-number>700</rec-number>foreign-keys=<key app="EN" db-id="v22aw5p0kf5fpve0sr8xxreie02sxs9z202x" timestamp="1472841023">700/key>/foreign-keys> ref-type name="Journal Article">17</ref-type> contributors=<authors>author>Lyon, David R</author>author>Alvarez, Ramón A</author>author>Zavala-Araiza, Daniel</author>author>Brandt, Adam

R</author><author>Jackson, Robert B</author><author>Hamburg, Steven  
P</author></authors></contributors><titles><title>Aerial surveys of elevated hydrocarbon emissions from oil  
and gas production sites</title><secondary-title>Environmental science & technology</secondary-  
title></titles><periodical><full-title>Environmental Science & Technology</full-title><abbr-1>Environ. Sci.  
Technol.</abbr-1><abbr-2>Environ Sci Technol</abbr-2></periodical><pages>4877-  
4886</pages><volume>50</volume><number>9</number><dates><year>2016</year></dates><isbn>0013-  
936X</isbn><urls></urls></record></Cite></EndNote>].

X-axes are organized by decile, and the median of each decile is shown.

### 3.11. Final Anonymized Dataset

A final anonymized dataset from this study is available at [ [HYPERLINK "https://usu.box.com/v/2018-USU-IRsurvey"](https://usu.box.com/v/2018-USU-IRsurvey) ].

**Commented [CKB24]:** Will the entire anonymized dataset be available here or just two example Aerial Surveys videos and the Propane release videos?

## 4. Conclusions

The Aerial Survey portion of this study detected emissions at a very low percentage of well pads (0.5%) compared to a previous aerial survey [ ADDIN EN.CITE <EndNote><Cite><Author>Lyon</Author><Year>2016</Year><RecNum>700</RecNum><DisplayText>(Lyon et al., 2016)</DisplayText><record><rec-number>700</rec-number><foreign-keys><key app="EN" db-id="v22aw5p0kf5fpve0sr8xxreie02sxs9z202x" timestamp="1472841023">700</key></foreign-keys><ref-type name="Journal Article">17</ref-type></contributors><authors><author>Lyon, David R</author><author>Alvarez, Ramón A</author><author>Zavala-Araiza, Daniel</author><author>Brandt, Adam R</author><author>Jackson, Robert B</author><author>Hamburg, Steven P</author></authors></contributors><titles><title>Aerial surveys of elevated hydrocarbon emissions from oil and gas production sites</title><secondary-title>Environmental science & technology</secondary-title></titles><periodical><full-title>Environmental Science & Technology</full-title><abbr-1>Environ. Sci. Technol.</abbr-1><abbr-2>Environ Sci Technol</abbr-2></periodical><pages>4877-4886</pages><volume>50</volume><number>9</number><dates><year>2016</year></dates><isbn>0013-936X</isbn><urls></urls></record></Cite></EndNote>], at which more than 6.5% of pads in the Uinta Basin had detectable emissions. Part of the reason for this discrepancy was likely changes in well pad properties (wells in this study were older and lower-producing), but this study also had limits of detection that were between 2.5 and 7 times worse because of cold air temperatures.

The Ground Survey A&B portion of this study detected emissions at 31% of well pads. Infrared camera emissions detection surveys performed from the ground have much better limits of detection than aerial surveys (at least 10 times better in our controlled propane release study).

Qualitatively small and medium plumes were less likely to be reported as the distance between the camera operator and the well pad increased, and small and medium plumes were never observed at a distance greater than 103 m.

Well pads with detected emissions in the ground and aerial surveys had higher oil and gas production, were younger, and had more liquid storage tanks per pad relative to the entire surveyed population. Oil

well pads with higher oil production were more likely to have qualitatively large plumes, while gas well pads with higher gas production were more likely to not have any detectable plumes.

As has been shown in previous studies [ ADDIN EN.CITE ADDIN EN.CITE.DATA ], the majority of observed emission plumes in this study were from liquid storage tanks (75.9% of all observed plumes), including thief hatches, pressure relief valves, and tank piping.

Well pads with emissions control devices on tanks were more likely to have detected emissions in the ground and aerial surveys, had more detected emissions per pad, and were more likely to have emission plumes that were qualitatively categorized as large. As with the entire population of surveyed well pads, emissions from pads with tank controls originated mostly from tanks (78.1%), as was shown in a previous study [ ADDIN EN.CITE

<EndNote><Cite><Author>Mansfield</Author><Year>2017</Year><RecNum>965</RecNum><DisplayText>(Mansfield et al., 2017)</DisplayText><record><rec-number>965</rec-number><foreign-keys><key app="EN" db-id="v22aw5p0kf5fpve0sr8xxreie02sxs9z202x" timestamp="1531948429">965</key></foreign-keys><ref-type name="Report">27</ref-type><contributors><authors><author>Mansfield, M. L.</author><author>Lyman, S. N.</author><author>O'Neil, Trevor</author><author>Anderson, Randy</author><author>Jones, C.</author><author>Tran, H.</author><author>Mathis, J.</author><author>Barickman, P.</author><author>Oswald, W.</author><author>LeBaron, B.</author></authors></contributors><titles><title>Storage Tank Emissions Pilot Project (STEPP): Fugitive Organic Compound Emissions from Liquid Storage Tanks in the Uinta Basin</title></titles><dates><year>2017</year></dates><pub-location>Vernal, Utah</pub-location><publisher>Utah State University</publisher><urls><related-urls><url>https://documents.deq.utah.gov/air-quality/planning/technical-analysis/DAQ-2017-009061.pdf</url></related-urls></urls></record></Cite></EndNote>]. Well pads with tank controls tend to produce higher volumes of oil and gas than wells without tank controls.

Significant differences in the average number of detectable emission plumes per pad, and in the qualitative severity of those plumes, were found among oil and gas companies whose well pads were included in this study. This study is inadequate to ascertain the causes of those differences.

Repairs made by oil and gas companies in response to emissions detected ranged from small maintenance and repair work that cost between zero and a few hundred dollars, to replacement of thief hatches that cost several thousand dollars. Most repairs reported cost well under \$1,000 and were completed within 43 days.

## 5. Acknowledgments

This project was funded by the U.S. Bureau of Land Management, the Utah Legislature, the Utah Division of Air Quality, and the U.S. Environmental Protection Agency. It was carried out in cooperation with and under direction from the Ute Indian Tribe and the funding agencies. Personnel employed with these organizations and David Lyon of the Environmental Defense Fund provided helpful comments and assistance in this work. We are grateful to the many oil and gas companies who participated in this project by providing information about the emissions we observed and by providing comments on drafts of this document. We acknowledge the efforts of Colleen Jones, Trevor O'Neil, Randy Anderson (of Utah



State University), and Lexie Wilson (of the Utah Division of Air Quality), who completed the fieldwork for the ground survey.

## 6. References

---

[ ADDIN EN.REFLIST ]

**Commented [CKB25]:** For the Mansfield STEPP Study – could a web link be provided?